

# COMPACTCUT 202 E

# LISSMAC


CONSTRUCTION TECHNOLOGY

ROBUST, HIGH-PERFORMANCE ELECTRIC FLOOR SAW –  
IDEAL FOR CUTTING WORK INSIDE BUILDINGS

- Floor saw in robust and compact construction
- The smooth raising and lowering of the saw blade with a closed threaded spindle prevents damaging of the saw blade
- Adjustable cutting depth indicator for all saw blade diameters
- A large water tank reduces work interruptions
- The water cooling system provides an optimum saw blade cooling, this guarantees a longer saw blade life
- Blade guard easily foldable
- Simple service operations - good access to engine and cutting shaft
- With a parking brake
- Height adjustable handles for ergonomic operation
- Connection for external water supply with separately adjustable water tap
- The anti-vibration handle reduces vibrations to the operator, improving working conditions.



TECHNICAL DATA	COMPACTCUT 202 E
cutting depth max.	200 mm
cutting depth setting	stepless threaded spindle with depth gauge
saw blade Ø max.	500 mm
saw blade holder	25.4 mm
drive motor	electric
output power max.	5 kW
voltage	400V / 32 A
saw blade speed	2450 1/min.
dimensions (L/W/H)	1195/620/1010 mm
weight	115 kg



#### FLOOR SAWS

NR.

COMPACTCUT 202 E without diamond blade, incl. blade guard 500 mm

1094058

TOOL RECOMMENDATION	Ø in mm	Segments(LxWxH)	No.	Bore hole	Article No.
TRENDLINE ASPHALT	450	40 x 3,6 x 10	28	25,4 mm	791121
TRENDLINE ASPHALT	500	40 x 3,6 x 10	30	25,4 mm	791122
TRENDLINE CONCRETE LASER	450	40 x 3,6 x 10	32	25,4 mm	791149
TRENDLINE CONCRETE LASER	500	40 x 4,0 x 10	36	25,4 mm	791151